



st. cloud window

SCW5000 Sliding Glass Door



Product

- Frame depth 5"
- Nominal 0.08" wall thickness
- AW-PG 40
- STC 34-41
- OITC 26-33
- U-Value 0.33-.51

Applications

- All purpose
- Acoustic
- Impact

Configurations

- 2-lite
- 3-lite
- 3-lite center slide
- Impact



st. cloud window

390 Industrial Blvd, Sauk Rapids, MN 56379
800.393.9311 | www.stcloudwindow.com

SCW5000 Sliding Glass Door



Features

- 6063-T6 Aluminum alloy
- PA-66 Insulbar structural strut thermal barrier
- Polyamide covered steel adjustable rollers with sealed ball bearings for longer life and easy operation
- Integral 100% woven pile weather stripping for minimal air infiltration
- Extruded aluminum corner keys provide joint strength and alignment
- Integral weep system for superior water penetration resistance
- High performance 70% Kynar (AAMA 2605) paint, and Class I anodized finishes
- Eurogroove locking system hardware

Glazing

- 1" - 1.5" overall thick IG glass, factory glazed

Optional Features

- Exterior profiles: Custom shapes, interior trims, and mullions to meet design specifications and for added strength
- Glazing: High-performance, double, triple insulated, and impact glass as well as tints, low-e, tempered, and laminated.
- Finish: Anodized or high-performance paint finishes, custom colors, and split finishes.
- Accessories: Simulated divided lite muntin grids, removable panels, and insect screens

Performance Data (2-lite configuration)

U Value	SHGC	STC	OITC	Air Infiltration @ 6.24 lbf/ft ²	Water Penetration	Structural Load Pressure	Condensation Resistance (CR)	Test Size (inches)
.33-.51	.14-.55	34-41	26-33	0.175 cfm/ft ²	9.81 psf	±120 psf	45-47	122" x 95"

Performance results may vary based on frame and glazing options.

For the most current product information visit www.stcloudwindow.com or contact your sales representative.

