

SCW4500 Storefront & Entrance System



- ➤ Cutting Edge Design
 - Glass-reinforced polyamide thermal break
 - Factory assembled or Knocked down options
- Engineering and Design Assistance available



SCW4500 Storefront & Entrance System



St. Cloud Window storefront and entrance system provides thermal efficiency for the entire building envelope.

Glass-reinforced polyamide thermal struts provide the highest performing thermal barrier system, numerous shapes and profile choices, and split finish options.

Factory-assembled system is delivered ready for install. Also available as a knock-down (KD) option.


The system creates a single source package to fully integrate with other St. Cloud Window products.


Features

- Frame depth 4.5"
- Wall Thickness 0.125"
- 6063-T6 Aluminum alloy
- Thermal barrier: PA-66 Insulbar structural strut
- Weather stripping: Integral 100% woven pile for minimal air infiltration
- Extruded aluminum alignment keys to maximize strength
- Integral weep system for superior water penetration resistance
- High performance 70% Kynar (AAMA 2605) paint, Class I anodized finishes
- Vertical or horizontal mullion options to meet design specifications and for added strength
- Exterior profiles customized for specific historic requirement


Glazing


• I" overall thick IG glass, factory glazed








DOOR MEETING RAIL














STOREFRONT

SCW4500 Storefront & Entrance System

Optional Features

• Profiles: Exterior panning in custom shapes, interior trims, and mullions

• Glazing: High performance, double, and triple insulated glass as well as tints, low-e, tempered,

and laminated

• Finish: Anodized or high performance paint finishes, unlimited colors, dual/split colors and

finishes

• Accessories: Simulated divided lite muntin grids, rail fins, acoustic seals, and hardware

